



Mould Oil 222

DESCRIPTION

Medium viscosity, non-regulated mould release fluid which has proven effective in separating concrete from steel and plastic moulds and dyes. **Mould Oil 222** can be used in many other release applications, however as mixtures can vary, it is recommended that the fluid be trialled before long-term use.

FEATURES

- Non-regulated for storage and transport.
- Provides good penetration into moulds and parting surfaces.
- Easy to apply via brushing, swabbing or conventional spray systems.
- Competitively priced.

Versatility – **Mould Oil 222** can be used in various mould release applications where concrete based slurries require separation from a mould prior to curing.

Penetration – **Mould Oil 222** will spread rapidly and uniformly over mould surfaces.

Dual Action – **Mould Oil 222** contains soap forming ingredients which provides thin-film lubrication on surfaces combined with the low frictional hydrocarbon carrier fluid.

PACKAGING

Mould Oil 222 is available in bulk, IBCs (1000 litre bulk containers), drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Mould Oil 222** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearance	clear to amber liquid
Specific Gravity.....	0.86
Flash Point.....	230°C
Pour Point	-15°C
Viscosity @40°C.....	18.2cSt



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033